



100% Water Based High Quality Lacquer for Wooden Materials

AquaLack® Finish

Contains 95% of pure Nano Acryl WP

Ready to be applied - Any kind of dilution will void the warranty

AquaLack Finish is a high quality lacquer for wooden surfaces. It gives the final smooth and elegant aspect, as well as protection to the wooden surface.

It's 100% water based, made from our green 100% acrylic, nano-pollution free nano-resin Nano Acryl HT.

For this reason it does not absorb UV rays as well as Infrared (heat), so it reduces drastically the effects of temperature fluctuation of the protected material.

It does not contain any contaminant component, is APE / APEO free, as well as heavy metals free (lead, cadmium, etc.) and is Low VOC.

It does not smell, it can be applied in interiors without the necessity to evacuate the area.

AquaLack Finish is an ecological coating, environmental friendly and absolutely non toxic.

AquaLack Finish can be applied on any kind of wooden materials, giving a final appealing appearance.

It can be applied in various coats, 2, 3 or more, depending of the final aspect you require for the furniture or the wooden surface in general.

AquaLack Finish resists :

Extreme Weather – Salinity and Humidity of Marine Environment
Pollution - Animal Waste - Bird Drops - Permanent Puddles - Inorganic acids

All Nasacoat Coatings are 100% Acrylic - 100% Water Based
Non Toxic - 100% Ecological = Environmental Friendly and Sustainable
as well as

100% Free of cheap monomers : Styrene, Vinyl and VEOVA
100% free of poisoning : Ammonia, Lead, Heavy Metals, Organic Vapors Emission = 0 VOC

Sustainable Materials for a Better and Healthy Future



100% Water Based High Quality Lacquer for Wooden Materials

AquaLack® Finish

Contains 95% of pure Nano Acryl WP

Ready to be applied - Any kind of dilution will void the warranty

Technical Characteristics

Yield per Liter (m ²)	4.0 - 6.1	Flexibility	180°
Content of Nano Acryl HT	95%	Adhesion Strength	> 8.7 MPa
VOC	< 70 g / L - Low VOC	Adhesion Strength x m ²	> 887 Tons
Density	1.50 g / ml	Temperature Resistance	- 25° / + 110°
Solids	39% - 41%	Touch Dry	20 mins.
Viscosity	4,200 - 5,200 cps	Total Drying	40 mins.
pH	8.0 - 9.5	Total Curing time	36 hours
Maximum Storing Time	12 months	Warranty	3 years
Maximum Storage Temperature	35°		

AquaLack Finish can be easily applied with common brushes or air sprayers. It does not need any dilution, it's ready to apply.

AquaLack Finish is normally applied with 2, 3 or more coats, depending of the nature of the substrate material and of the final aspect you want to obtain.

See the Application Manual at : www.nasacoat.com/en/application_manual.pdf

Exclusive Distributor in Mexico :

Nasacoat de México SA de CV Av. López Mateos # 2077 - Plaza del Ángel - Local 9 - Nivel 1,
 Jardines de Plaza del Sol - 44510 Guadalajara, Jalisco - Mexico

Phone : +52 33 3696 10 51 email : team@nasacoat.com www.nasacoat.com